IBAZ: Quickstart

Summary

IoT Bridge for Azure (IBAZ) is an application that connects to an MQTT Server and consumes MQTT Sparkplug messages from Edge devices.

These messages must be formatted as Sparkplug Templates which are defined in the Sparkplug Specification. The Templates are used to create the Models in Azure Digital Twins automatically with no additional coding or configuration. Then multiple instances of these Templates generate the Assets and start to populate with real time data sent on change only, thus significantly reducing the amount of data being sent to the cloud.

For further details on Azure Digital Twins terminology, refer to the Azure Digital Twins documentation. For further details on Eclipse Sparkplug, refer to the Eclipse Sparkplug resources.

This quickstart document covers how IoT Bridge can be used to consume MQTT Sparkplug data and create and update Azure Digital Twins Asset Models and Assets. This will show how to configure IoT Bridge as well as show how to use Inductive Automation's Ignition platform along with Cirrus Link's MQTT modules to publish device data to an MQTT Server. This data will ultimately be consumed by IoT Bridge to create and update the Azure Digital Twins components.

\odot	This tutorial will use the MQTT Distributor implementation however the IBAZ does work with any MQTT v3.1.1 compliant MQTT Server.
J	······································

Ignition in conjunction with Cirrus Link's MQTT Transmission module converts Ignition User Defined Types (UDTs) to Sparkplug Templates. This is done automatically by the MQTT Transmission module. So, much of this document will refer to UDTs rather than Sparkplug Templates since that is what they are in Ignition.

More information on Inductive Automation's Ignition platform can be found here. Additional information on Cirrus Link's MQTT Transmission module can be found here.

Step 1: IBAZ Installation

- Complete the IBAZ Installation process
- This will install the Virtual machine, Disk, Network interface and Public IP address resources

Step 2: Create an Azure Digital Twins instance

- If needed create following the Microsoft Set up an Azure Digital Twins instance and authentication (portal) instructions
- Collect the Host name as this is used in the IBAZ: Configuration

Step 3: Configure the Azure Digital Twins instance

- Assign the Azure Digital Twins Data Owner role to your Azure Active Directory app registration identity and an additional Azure user(s)
- Add a system-managed identity to your instance

Step 4: Create an event Hubs Namespace

· If needed create following the Microsoft Create an event hub using Azure portal instructions

Step 5: Create an Azure Data Explorer Cluster

If needed create following the Microsoft Create an Azure Data Explorer cluster and database instructions

Step 6: Configure the Azure Data Explorer Cluster

- Configure the database permissions to add your Azure Digital Twins Instance with a Database Admin role
- Add additional Viewer role(s) to be able to query data

Step 7: Configure the Azure Digital Twins instance data history connection

• Setup a data history connection

Step 8: Create an Azure Active Directory App Registration

- If needed create following the Microsoft Create an app registration to use with Azure Digital Twins instructions
- Collect the client ID, tenant ID and Client secret Value as these are used in the IBAZ: Configuration

In our example below we have all the resources in the same Resource group:

=	Microsoft Azure	${\cal P}$ Search resources, services, and docs (G+/)			Q Q	©	0	ন্দি	gill.houghton@cirr cirrus link sc	uslin Dlutions
Hom	ie >									
[*]	gmmøa⊑ng & ☆ … Resource group									×
٩	Search (Ctrl+/)	🕂 Create 🚳 Manage view 🗸 📋 Delete resource group 💍 Refresh 🞍 Export to CSV 😤 Open query	\oslash Assign tags $ ightarrow$ Move $ ightarrow$ 🗊 De	iete 🛓	Export tem	plate [Open	in mobi	le	
()	Overview	∧ Essentials							J.	SON View
	Activity log	Subscription (move) :	Deployments : 1 Succeeded							
°≈ /	Access control (IAM)	Subscription ID :	Location : West US 2							
	Tags	Tags (edit) : <u>Click here to add tags</u>								
4	Resource visualizer									
۶	Events	Resources Recommendations (1)								
Setti	ngs	Filter for any field Type equals all \times Location equals all \times $^+\!_{ abla}$ Add filter								
土 1	Deployments	Showing 1 to 9 of 9 records.			No grou	ping		\sim	≡≡ List view	\sim
0	Security	Name 1	Type 1.		Loca	ation 1.				
B (Policies		Vietual manhine		Was					
111	Properties	Develop-stagenot-bridge-4-azure-linux	Disk		Wes	1052				
۵ (Locks	Develop-stage-lot-bridge-4-azure-linux_Usbisk_1_/8c200c2e32/40a38529515edaa4ed9b	Disk		wes	1052				
Cost	Management	Develop-stage-lot-bridge-4-azure-linuxivetint	Network Interface		wes	1052				
\$ O	Cost analysis		Azura Digital Twing		Wes	+116.2				
1	Cost alerts (preview)		Event Hubs Namesnace		Wes	+115.2				
ا (3)	Budgets		Azura Data Evolorar Cluster		Wes	+115.2				
	Advisor recommendations		Network security group		Wes	+115.2				
Mon	itoring	→ sectodiver	Virtual network		Wes	t US 2				
	nsights (proview)									
	Alorte	< Previous Page 1 V of 1 Next >							Sive f	eedback
cá l	Metrics									

Step 9: Install Ignition and MQTT Modules

For this setup, we'll install Inductive Automation's Ignition platform along with the MQTT Distributor (MQTT Server) and MQTT Transmission (Edge device) modules from Cirrus Link.

Installation of Ignition is very straightforward following the instructions in the Installing and Upgrading Ignition guide.

With Ignition installed, the Cirrus Link modules must be installed as a plugin to Ignition. Follow the instructions in our Module Installation guide.

Step 10: IBAZ Configuration

Update your configuration properties in the IBAZ configuration file located on the VM at /opt/ibaz/conf/ibaz.properties. Instructions for accessing the VM can be found here.

Follow our IBAZ configuration guide for details.

M With the default MQTT Distributor configuration use the following properties:

mqtt_server_url = tcp://youripaddress of installed Ignition instance:1883

mqtt_username = admin

mqtt_password = changeme

Now the IBAZ service can be restarted to pick up the new configuration. Do so by running the following command.

sudo systemctl restart ibaz

At this point, IBAZ should connect to MQTT Distributor and be ready to receive MQTT Sparkplug messages. Verify by running the following command.

tail-f /opt/ibaz/log/wrapper.log

After doing so, you should see something similar to what is shown below.

Note the last line is 'MQTT Client connected to ...'. and this indicates that we have successfully configured IBAZ and properly provisioned MQTT Distributor.

🖉 ubuntu@ibaz. ~	-	×
Aug 25, 2022 11:09:43 FM org.rzo.yajsw.os.posix.PosixService getFid		^
INFO: wrapper pid file: /run/wrapper.ibaz.pid		
Service ibaz started		
ubuntu@ibaz:~\$ tail -f /opt/ibaz/log/wrapper.log		
INF0 28265/0 22-08-25 23:09:47 23:09:47.275 [main] INF0 c.c.i.a.model.DigitalTwinInfoModel - Creating 1 EdgeNode Info Digital Twin Models		
INF0 28265/0 22-08-25 23:09:47 23:09:47.307 [main] INFO c.c.i.common.info.Diagnostics - Creating or updating Bridge Model instances		
INF0 28265/0 22-08-25 23:09:47 23:09:47.307 [main] INF0 c.c.i.a.model.DigitalTwinInfoModel - Creating IBAZ Info Digital Twin: IBAZ Metrics IBAZ Info Gill IBAZ Instance		
INF0 28265/0 22-08-25 23:09:47 23:09:47.365 [main] INFO c.c.i.common.info.Diagnostics - Creating or updating MQTT Client Model instances		
INFO 28265/0 22-08-25 23:09:47 23:09:47.365 [main] INFO c.c.i.a.model.MgttClientInfoModel - Getting MQTT Client Info instance		
INF0 28265/0 22-08-25 23:09:47 23:09:47.365 [main] INF0 c.c.i.a.model.DigitalTwinInfoModel - Creating MQTTClient Info Digital Twin: IBAZ_Metrics_MQTT_Client_Info_Gill_IBAZ_Instance		
INF0 28265/0 22-08-25 23:09:47 23:09:47.430 [main] INF0 c.c.i.common.AbstractSparkplugClient - MQTT Client IBAZ-b410439b-dfd6-4c9d successfully started		
INF0 28265/0 22-08-25 23:09:47 main method terminated		
INF0 28265/0 22-08-25 23:09:47 exit on main terminate -1		
INF0 28265/0 22-08-25 23:09:47 23:09:47.431 [Thread-9] INFO org.eclipse.tahu.mqtt.TahuClient - IBAZ-b410439b-dfd6-4c9d: Creating the MQTT Client to tcp://52.91.136.214:1883 on thread	Thread-	
INF0 28265/0 22-08-25 23:09:47 23:09:47.921 [MQTT Call: IBAZ-b410439b-dfd6-4c9d] INF0 org.eclipse.tahu.mqtt.TahuClient - IBAZ-b410439b-dfd6-4c9d; connect with retry succeeded		
INF0 28265/0 22-08-25 23:09:47 23:09:47.921 [MOTT Call: IBAZ-b410439b-dfd6-4c9d] INF0 org.eclipse.tahu.mgtt.TahuClient - IBAZ-b410439b-dfd6-4c9d: Connected to tcp://52.91.136.214:1883		
INF0 28265/0 22-08-25 23:09:47 23:09:47.921 [MOTT Call: IBAZ-b410439b-dfd6-4c9d] INF0 c.c.i.common.AbstractMessageCallback - Connection complete to Local MOTT Server		
INF0 28265/0 22-08-25 23:09:48 23:09:48.446 [Thread-9] INF0 org.eclipse.tahu.mqtt.TahuClient - IBAZ-b410439b-dfd6-4c9d: MQTT Client connected to tcp://52.91.136.214:1883 on thread Thr	ead-9	
		\sim

Now we can configure our Ignition MQTT Transmission module to connect to the MQTT Distributor server in order to publish data into Azure. We will also import some UDT Definitions and UDT Instances that will be mapped to Azure Models and Digital Twins.

Step 11: Import UDTs and tags

For this quick start, we have created a number of sample UDTs and associated tags that can be easily imported. Using the Ignition Designer, import these UDTs and tags into the default Tag Browser.

IBAZ_quickstart_UDTs.json

IBAZ_quickstart_tags.json

Once imported, you can browse into each tag to see the structure of the UDT and UDT Instances.



Step 12: Edge Device Configuration

Now we can configure the MQTT Transmission module to connect to MQTT Distributor. From the left hand menu bar in Ignition, select MQTT Transmission > Settings.

Select the Transmitters tab and edit the Default Transmitter by setting the following properties:

- Tag Path = Azure Smart Factory
- Convert UDTs = Unchecked
- Publish UDT Definitions = Checked
- Optimize UDTs = Checked

Once this configuration is saved, you can confirm you are connected by switching to the Servers tab and verifying that the Connected status shows 1 of 1

← -	→ C O	localhost:8088/web/config/mqtttransmission.settings?20	☆	
/ Edgel				Log Out≜admin Log Out
Ignit	tion		Help 🕜	Get Designer
♠	SYSTEM	Config > Mqtttransmission > MQTT Transmission Settings		
lome	Overview	Trial Mode 1:43:56 We're glad you're test driving our software. Have fun.		Activate Igniti
հո	Backup/Restore			
tatus	Ignition Exchange			
\$	Licensing	General Servers Sets Transmitters Records Files		
Config	Modules			
	Projects	Settings Certificates		
	Redundancy			
	Gateway Settings	Name IIPI ServerSet licename Connected		
	NETWORKING			
	Web Server	Distributor tcp://localhost:1883 Default admin 1 of 1	delete	edit
	Gateway Network			
	• Count	→ Create new MQTT Server		

Step 13: Confirm connection with the Azure Digital Twins Explorer

Navigate to your Azure Digital Twins Explorer by clicking on the Overview for your Azure Digital twins and selecting the Open Azure Digital Twins Explorer (preview) link at the top

\equiv Microsoft Azure	${\cal P}$ Search resources, services, and docs (G+/)		Þ.	Q	۵ ۵	0	ন্দ	gill.houghton@cirruslin
Home >								
Azure Digital Twins	☆☆…							×
P Search (Ctrl+/) ≪	📋 Delete 🕘 Open Azure Digital Twins Explorer (p	view)						
less Overview	↑ Essentials							JSON View
Activity log	Resource group (move) : gill.ibaz.rg	Provisioning state : Activ	ve					
Access control (IAM)	Location : West US 2	Host name : c'						
Tags	Subscription (move) : <u>Cirrus-Link-Primary-Subscrip</u>	on System-assigned ID : 1			-			
Diagnose and solve problems	Subscription ID : e							
	Tags (edit) : <u>Click here to add tags</u>							
Settings	Metrics Get Started							
💲 Identity								
Networking	Learn	t started with Azura Digital Twins						
Properties	G	et started with Azure Digital Twills						
🔒 Locks	Access	s next? The first step is deciding how to make Azure Digital Twins work for you. To	save you tim	e searchi	ing,			
Connect outputs	Build We'	curated a list of the most important articles to start with. Or, check out our full doc	c set and exp	lore on y	our			
1 Endnoints	r Integrate	The second s						•

This will display the Azure Digital Twins Explorer view:

٩	Azure Digital Twins Explorer Prev	iew	digitaltwins-pu7yy2jgsdvg2		ê ©	? ©	Gillian Houghton $ R_{\! a} $
≡	QUERY EXPLORER						
4	Saved Queries \checkmark	SELECT * FROM digitaltwins				Overlay results	Run Query
6 8	TWINS MODELS	TWIN GRAPH MODEL GRAPH					
ŧ		₩ \$dtld	✓ Φ Φ ∞ % 1 % ✓	₽×≫			
Ş		 α α α ω φ Υ 					

Run Query as SELECT * FROM digitaltwins and you will see two digital twins created; one for the IBAZ instance and one for the connected MQTT Client

4	Refer to the IBA2: Mappings and Constraints document for details on digital twin properties										
٩	Azure Digital Twins Explorer Preview				digitaltwins-pu7yy2jgsdvg	n2 🤀 📼	Ū 43	?	©	Gillian Houghton	ዲ
≡ ⊶4	QUERY EXPLORER Saved Queries	ELECT * FROM digitaltwins						Overlay re	sults 🗌	Run Query	8
තී	TWINS MODELS	TWIN GRAPH MODEL GRAPH									
đ		IBAZ.Metri	🖈 \$dtld	✓ Φ Φ Φ	ጿ 1 ፝፝፝፝፝፝፝፝፝፝፝፝፝፝፝፝፝ ₩ ~ ₩ ~ ≫	TWIN PROPERTIE	s				
₿÷		 ■ 	IBAZ_Met	tri tri		<pre>\$dtld: IBAZ_ # Connected # InstanceCo = LastError: # Measuremu # ModelCour # ModelCou</pre>	Metrics_IBAZ_ tdgeNodes: 0 N/A entCount: 0 entUpdateCount: t: 0 ageCount: 0 ss: False × tdd: ff-78c8-4 :	Enfo_Gill_IBA	Z_Insta X X X X	nce c"	

From Ignition Designer, refresh Transmission to publish the edge node tags to Azure

Run Query as SELECT * FROM digitaltwins and also refresh your MODELS. Now you will see that that Digital Twins have been created for each of your UDT Instances and an addition digital twin containing metrics for the edge node.



You can drill into each Digital Twin by selecting the twin and verifying the associated data by checking the Twin Properties. From the Edge Device, change the tag values and see that they are updated.



A You will need to Run Query each time to see refreshed data through the Azure Digital Twins Explorer UI.

If you looking to query data on a single digital twin, you can modify the query using the WHERE statement for example: SELECT * FROM digitaltwins WHERE \$dtld = 'Smart_Factory_1%2FFactory_Energy%2FLine_3%2FPaint_Booth'

Step 14: Confirm data in database

Navigate to your Azure Data Cluster Explorer and select Databases from the left hand menu bar.

	$\mathcal P$ Search resources, serv	ces, and docs (G+/)		∑ (7 Q	۵.	୭ ନ	gill.houghton@cirruslin CIRRUS LINK SOLUTIONS
Home > gill.ibaz.rg >								
Azure Data Explorer Cluster	☆ ☆ …							×
	$+$ Add Database \square Stop \circlearrowright Refresh \rightarrow Move	💛 📋 Delete 🔗 Feedback						
Security + networking								JSON View
A Permissions	Resource group (move) :		State : Running					
💲 Identity	Location (move) : West US 2		URI : I			-		
A Encryption	Subscription (move) : (Data Ingestion URI :	-				
Security	Subscription ID : e		Compute specifications : Standard_D12_v2					
Networking	Engine type : V3		Instance count : 2					
Data	See more	Data						
Databases	Getting started Overview Tutoriais & Demos	Data						
Monitoring	Summary							
Insights	Resource health	Advisor recommendations	Scale out		m I	Insights		
💵 Alerts	Watches your resource and tells you if it's	 0 cost recommendations 	Scale your cluster instance count automatically	6		Get more vis	ibility into th	e usage, performance,
🖬 Metrics	Available	0 performance recommendations 1 operational excellence	A Manual coals (2 instances)				.,	
Diagnostic settings	Avaliable	recommendations	 Manual scale (2 instances) 					
🧬 Logs								
Advisor recommendations	Explore in Azure Data Explorer							
Morkbooks	🖉 🖉 Query your data							
Automation	Open dashboards							
🖧 Tasks (preview)								
😫 Export template								
· · · · · · · · · · · ·	Monitoring summary							

Click on the link for your database and select Query from the left hand menu bar:

		$\mathcal P$ Search resources, services, a	nd docs (G+/)				⑦ & gill.houghtor CIRRUS	1@cirruslin
Home > gill.ibaz.rg >								
Azure Data Explorer Cluster	Databases							×
	« 🕂 🕂 Add Database 💍 Re	fresh 🛍 Delete						
🔉 Overview	Search to filter items							
Activity log								
Access control (IAM)	Database ↑	Size	Retention period	Cache period	Database kind	Shared with others	Relationship	
Tags	kustodb	5.8 MB	unlimited	unlimited	Read-Write	No	None	
Diagnose and solve problems								
JII Query								
Settings								
🔀 Scale up								
Scale out								
🚔 Configurations								
Se Properties								
🔒 Locks	•							

=	Microsoft Azure	,₽ Search resources, services, and docs (G+/)						3 0	ন্থ	gill.houghton@cirruslin CIRRUS LINK SOLUTIONS
Hom	e >									
<u>※</u>	kustodb (Azure Data Explorer Database	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,								×
۶	earch (Ctrl+/) «	🕞 Query 🖉 Edit 💍 Refresh 📋 Delete								
🔊 с	Verview									JSON View
Overv	view	Resource group (move) : gill.ibaz.rg		Retention period (in days) : unlimited						
Åq ₽	ermissions	Location (move) : West US 2 Cache period (in days) : unlimited								
周 (Juery	Subscription (move) : Cirrus-Link-Primary-Subscription Database kind : Read-Write								
_		Subscription ID :		Shared with others : No						
Settir	igs	Data connections								
βu	ocks									
ø	ata connections	- Fundlish	Event Cold (Black stormer)	and to T that						
₿ P	roperties	Event Hub	Event Grid (blob storage)							
Autor	mation	1	0	0						
🖧 т	asks (preview)									

You can now query the data using the Azure Data Explorer tooling to view the data from each of the digital twins.

Data received by Azure Digital Twins Explorer can take up to 5 minutes to be available in Azure Data Explorer

. 0 × +				卮 1~ り? 🤅
🖬 Open in Web Ul 📃	« ▷ Run 🔊 Recall Scope: (and the second		👌 File 🗸 🖄 Share 🛇
∑ Filter 5	1 adt_dh_digitaltwins_p 7,,^jo ' o^ i o^_ 2 take 1000			
✓ □ ✓ □ kustodb	I Table 1		🔎 Search 🕑	Done (0.272 s) 🕮 1000 records 🐵 📋 🚍 🗸 🕫
> I adt_dh_digitaltwins	TimeStamp ↓	Modelld =	Key 📃	Value
> III RawEvents	> 2022-08-29 19:00:20.1550	dtmi:domain:Conveyor;1	Temperature	{"engUnit":"degF","value":12.5,"quality":"STALE"}
	> 2022-08-29 19:00:20.0190	dtmi:domain:Paint_Booth;1	Outlet_Motor_Amps	{"engUnit":"amps","value":9,"quality":"STALE"}
	> 2022-08-29 19:00:19.8160	dtmi:domain:Paint_Booth;1	Temperature	{"engUnit":"degF","value":125,"quality":"STALE"}
	> 2022-08-29 19:00:19.7780	dtmi:domain:Paint_Booth;1	Inlet_Blade_RPM	{"engUnit":" rpm", "value":1578, "quality":"STALE"}
	> 2022-08-29 19:00:19.6870	dtmi:domain:Conveyor;1	Motor_RPM	{"engUnit":" rpm", "value":114, "quality":"STALE"}
	> 2022-08-29 19:00:19.6450	dtmi:domain:Conveyor;1	Motor_AMPS	{"engUnit":"amps","value":12,"quality":"STALE"}
	> 2022-08-29 19:00:19.5930	dtmi:domain:Conveyor;1	Vibration	{"engUnit":"hz", "value":1300, "quality":"STALE"}
	> 2022-08-29 19:00:19.5490	dtmi:domain:Conveyor;1	Temperature	{"engUnit":"degF","value":89,"quality":"STALE"}
	> 2022-08-29 19:00:19.4840	dtmi:domain:Hauloff;1	Slide_Gate	{"engUnit":"status", "value":false, "quality":"STALE"}
	> 2022-08-29 19:00:19.4380	dtmi:domain:Hauloff;1	Receiver_Hopper	{"engUnit":"cnt","value":65.23,"quality":"STALE"}
	> 2022-08-29 19:00:19.3960	dtmi:domain:Hauloff;1	Valve	{"engUnit":"status", "value":1, "quality":"STALE"}
	> 2022-08-29 19:00:19.3370	dtmi:domain:Hauloff;1	Chrome_Roll	{"engUnit":"status", "value":true, "quality":"STALE"}
	> 2022-08-29 19:00:19.2980	dtmi:domain:Hauloff;1	Temperature	{"engUnit":"degF","value":23.023,"quality":"STALE"}
	> 2022-08-29 19:00:09.9930	dtmi:domain:EdgeNode;1	Connected	True
	> 2022-08-29 19:00:09.9930	dtmi:domain:EdgeNode;1	ConnectDateTime	2022-08-29T18:19:04.3710000Z
	> 2022-08-29 19:00:09.9930	dtmi:domain:EdgeNode;1	DisconnectDateTime	1970-01-01T00:00:00.0000000Z
	> 2022-08-29 19:00:09.9930	dtmi:domain:EdgeNode;1	BirthCount	1
	> 2022-08-29 19:00:09.9930	dtmi:domain:EdgeNode;1	DeathCount	0
	4			•

Now the data is in the cloud, there are existing Microsoft documentation useful for processing this data for managing anomaly detection, active monitoring and trending/reporting. The reference links are include below:

Anomaly detection

 \odot

- Multivariate Anomaly Detection in Azure Data Explorer
 - ADX contains native support for detecting anomalies over multiple time series by using the function <u>series decompose ano</u> malies().
- Time series anomaly detection & forecasting
 - This article details time series anomaly detection and forecasting capabilities of KQL.
- Active monitoring
 - Azure Data Explorer connector for Power Automate
 - Send notifications and alerts based on query results, such as when thresholds exceed certain limits.
- Trending and reporting

• Azure Data Explorer connector for Power Automate

- Send regular, such as daily or weekly, reports containing tables and charts.
 Azure Data Explorer data visualization
 - - Data visualization and reporting is a critical step in the data analytics process. Azure Data Explorer supports many BI services so you can use the one that best fits your scenario and budget.